DOOR SCHEDULE

	DOOR								FRAME				HARDWARE				RE			
	NO.	TYP	Έ	SIZE		THICKNESS	MATERIAL	CORE	FINISH	TYPE	MATERIAL	GA.	FINISH		WALL DOOR STOP	FLOOR DOOR STOP	LOCKSET	PASSAGE	PRIVACY	REMARKS
	101	w		3'-6" x 7'-0"	-	1-3/4"	WOOD / BIRCH	SOLID	STAINED	2	STEEL	16	PAINTED		•		•	•		WAITING
	102	W		3'-6" x 7'-0"	-	1-3/4"	WOOD / BIRCH	SOLID	STAINED	2	STEEL	16	PAINTED		•		•	•		RECEPTION
	103	RW)	3'-0" x 7'-0"		1-3/4"	WOOD / BIRCH	SOLID	STAINED	(R/1)	STEEL	16	PAINTED		•		•	和大大学		ÖFFICE
	103A		- 1 -		_	9					<u>/1</u>									(EXISTING) CLOSET
	104	RW)	3'-0" x 7'-0"		1-3/4"	WOOD / BIRCH	SOLID	STAINED	(R/1)	STEEL	16	PAINTED							DOCTOR OFFICE
	105	E1		4'-0" x 7'-0"	-															M.R.I SHIELDED DOOR SUPPLIED BY SHIELDING VENDOR / STAINED BY CONTRACTOR
	106			3'-0" x 7'-0"		1-3/4"	WOOD / BIRCH	SOLID	STAINED	5.5	STEEL	16			•		•			CONTROL ROOM
1	106A	R/W		3'-0" x 7'-0"		1-3/4"	WOOD / BIRCH	SOLID	STAINED	R/1	STEEL	16	PAINTED					•		CLOSET /1
ス ス	107	RW	V	3'-6" x 7'-0"		1-3/4"	WOOD / BIRCH	SOLID	STAINED	{ R/1 {	STEEL	16	PAINTED							PET/MRI.
	108	RM	3	3'-0" x 7'-0"	1=1	1-3/4"	WOOD / BIRCH	SOLID	STAINED	R/1	STEEL	16	PAINTED		•		•			ULTRASOUND
	.109	E2		3'-0" x 7'-0"		1-3/4"	WOOD/BIRCH	SOLID	STAINED	3E ∴	STEEL	:- 16 ds	PAINTED	4 77 3 59	外外的					P.E.T SHIELDED DOOR SUPPLIED BY SHIELDING VENDOR // STAINED BY CONTRACTOR
<u> </u>			X 2 2 2 2 2 2 2		•								TO SERVICE OF SERVICE		N		Chia Marcinosi di	aranani wa alikuwa		
ST	411.5	RW	()	3'-0" x 7'-0"		1-3/4"	WOOD / BIRCH	SOLID	STAINED	(R/1)	WOOD	1 2 m/2 m	PAINTED				j		•	DRESSING
FIR	112	RW	()	3'-0" x 7'-0"	-	1-3/4"	WOOD / BIRCH	SOLID	STAINED	(R/1)	STEEL	16	PAINTED	Let Lave on the second	•			on Voltage or ≥ the two	ain icita axe	TOILET
	113	RW	7 11	3'-0" x 7'-0"		1-3/4"	WOOD / BIRCH	SOLID	STAINED	> R/1 {	/1\ STEEL	4/4/16/	PAINTED	4 4 5 5 5 5	*•		74 PAR 5			QUIET RM - SHIELDED DOOR SUPPLIED BY SHIELDING VENDOR / STAINED BY CONTRACTOR
	114	RM	<u>'</u>	3'-0" x 7'-0"	-	1-3/4"	WOOD / BIRCH	SOLID	STAINED	(R/1 \)	STEEL	16	PAINTED	Fig. 5. Social Metals	-X : 325250	1 (72) (7) (2) (3)	(acaranii 200 20	40 201232004	TOILET - SHIELDED DOOR SUPPLIED BY SHIELDING VENDOR / STAINED BY CONTRACTOR
	115	(RW	()	3'-0" x 7'-0"		1-3/4"	WOOD / BIRCH	SOLID	STAINED	(R/1)	STEEL	16	PAINTED		•		W.		•	COLOR DE LONGUES DE LA COMPANIA DE PROPERTO ANTICONO DE LO COLOR DE LA COLOR DEL COLOR DE LA COLOR DE LA COLOR DEL COLOR DE LA
	116	E2	trade Control to to	2'-6" x 7'-0"	-	1-3/4"	WOOD / BIRCH	SOLID	STAINED	4E	STEEL	16	PAINTED	A HES OF PERSON	124 L. C. C. C.		●		35 35 325	P.E.T. / C.T. CLOSET
	4117	W		2'-6" x 7'-0"		1-3/4"	WOOD/BIRCH	SOLID	STAINED	4.1	STEEL:	16:11	PAINTED		g spec	N. Por William	38.93	å	一种	CLOSET
	al artif il day				-							Latin San San San San San	of the second of	eres responsible		Spire than the state of the	10 L 10 L	-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1	in techniques	
	119	RW	/ 1	3'-0" x 7'-0")	1-3/4"	WOOD / BIRCH	SOLID	STAINED	(R/1)	1 STEEL	16	PAINTED			•			•	BREAK ROOM
	* 15° ± 5. ±		¥3 4 3.00 013	Karmethal Les Barta Les	-					1.3520.0				21.1)		A-2-13			
	121	E2	\ \ \	3'-0" x 7'-0"		1-3/4"	WOOD / BIRCH	SOLID	STAINED	1E	STEEL	16	PAINTED				/●	272-10-14-		X-RAY - SHIELDED DOOR SUPPLIED BY SHIELDING VENDOR / STAINED BY CONTRACTOR
	122	R/W	/ /1	3'-0" x 7'-0"	-	1-3/4"	WOOD / BIRCH	SOLID	STAINED	(R/1/	/1\ STEEL	16	PAINTED		25 SO S	G G-Pale street		JA 15 JA 16 J	• • • • • • • • • • • • • • • • • • •	DRESSING
		100		STATING	-					1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1							7 3 3	•		VECTION
	A	A2		EXISTING	- 	-	-	-					- Nederland of the second		on cutylete		is is a second		5 4 44	VESTIBULE
	- B, _U	A2		EXISTING		•	1969 - 1969								50 V 1 V 100 VS 100 V 100		3.5	•		LOBBY EXTERIOR
	С	RW		EXISTING 3'-0" x 7'-0"	- 1.736, 42 tol.42	1-3/4"	- WOOD / BIRCH	SOLID	STAINED	(BM)	1 STEEL	16	PAINTED	N. B. Transford Springs		i lata da da	ingle et al.		ži seriasias	REAR EXIT
	FD	A2		EXISTING		A A COMPLETE WAS TO SECURE			- STAINED	CON	X 1700 ACCT 12 1511	\$5.201 0 2.22	SPACOLO CO							EXTERIOR
	NO.			SIZE	RATING	THICKNESS	MATERIAL	CORE	FINISH	TYPE	MATERIAL	GA.	FINISH		WALL DOOR STOP	FLOOR DOOR STOP	LOCKSET	PASSAGE CLOSER	PRIVACY	REMARKS

HARDWARE GENERAL NOTES:

FLOOR

- 1. ALL DOOR HINGES TO BE STEEL BALL BEARING FULL MORTISE TYPE
- 2. ALL METAL DOOR FRAMES TO BE PROVIDED W/ SILENCERS.
- 3. ALL CYLINDRICAL LOCK SETS & LATCH SETS TO BE COMMERCIAL GRADE, LEVER HANDLED HARDWARE. 4. ALL DOORS TO BE PROVIDED WITH COMMERCIAL GRADE LEVER HANDLED HARDWARE, A.D.A.
- APPROVED W/ SATIN FINISH U.N.O. 5. ALL INTERIOR DOORS TO BE PROVIDED W/ COMMERCIAL GRADE WALL MOUNTED DOOR STOPS U.N.O.

BASE

6. ALL NEW INTERIOR WOOD DOORS TO BE SATIN GRADE IN KNOCKDOWN HOLLOW METAL FRAMES.

<u>WALLS</u>

7. MANUALLY OPERATED FLUSH BOLTS ARE NOT PERMITTED.

DOOR NOTES:

- 1. PROVIDE BLOCKING IN PARTITIONS WHERE DOOR WALL STOPS OCCUR.
- 2. COORDINATE DOOR UNDERCUTS WITH MECHANICAL PLANS.

DOOR FRAME NOTES:

- 1. PROVIDE RATED ASSEMBLIES AT ALL RATED OPENINGS.
- 3. ALL DETAILS REFERENCED IN DOOR SCHEDULE ARE SHOWN ON THIS
- SHEET U.N.O.

- 2. PROVIDE CONTINUOUS SEALANT AT ALL EDGES OF METAL FRAMES IN CONTACT WITH ADJACENT WALL SURFACES.
- 4. H.M. FRAMES PAINTED COLOR TBD.

FLOOR COVERING SPECIFICATIONS

RESILIENT FLOORING (V.C.T.)

TBD by OWNER. Armstrong World Industries, Inc., P.O. Box 3001, Lancaster, PA

phone: 800.233.3823

VINYL WOOD PLANK LAMINATE FLOORING

ROBINA VINYL LAMINATE, HEAVYWEIGHT SERIES, BOSTON CHERRY. Wood Floors Plus, 50 Orchard Road, Glen Burnie, MD 21060 phone: 410.636.9663

RUBBER WALL BASE

TBD by OWNER. Johnsonite, 16910 Munn Road, Chagrin Falls, Ohio 44023 phone: 800.899.8916

CARPET

PATCRAFT DESIGN WEAVE; STYLE 10246 APPROACH; COLOR 46201 LITERAL

PO Box 2128, Dalton, GA 30722-2128 phone: 800.241.4014


SHERWIN-WILLIAMS SHOJI WHITE SW70242 or TBD by OWNER. 1524 E Joppa Rd Spc D. Towson, MD 21286-5911 phone: 410.296.1040

CEILING SPECIFICATIONS


- I ARMSTRONG 24" X 48" WHITE 9/16 EXPOSED TEE WITH FINE-TEXTURED WHITE 'SECOND LOOK', SCORED NON-DIRECTIONAL PANELS BY ARMSTRONG OR EQUAL AS SELECTED BY OWNER.
- C-A1 | 24" X 48" WHITE 'SECOND LOOK', SCORED NON-DIRECTIONAL PANELS BY ARMSTRONG OR EQUAL INSTALLED IN EXISTING REFURBISHED AND REPAINTED CEILING GRID
- C-2 | NON-FERROUS LAY-IN ACOUSTICAL PANEL SYSTEM: ARMSTRONG 24" X 48" WHITE 9/16 EXPOSED TEE WITH FINE-TEXTURED WHITE 'SECOND LOOK', SCORED NON-DIRECTIONAL PANELS BY ARMSTRONG OR EQUAL AS SELECTED BY OWNER.
- C-3 | GYPSUM BOARD CEILING / BULKHEAD FACES. PAINTED WHITE - COLOR TBD. INSTALL USING NON-MAGNETIC FASTENERS AND ANCHORAGE

MILLWORK FINISHES


- L-1 FORMICA 837 "GRAPHITE"
- L-2 FORMICA 7759 "SELECT CHERRY"



STAIN GRADE SOLID W CORE WOOD DOOR



EXIST. ALUMINUM DOOR AND FRAME HARDWARE TO MATCH EXIST. STOREFRONT SYS.




MRI ROOM DOOR


LEAD SHIELDED DOOR

(E1

(E2




EXIST. ALUMINUM A2 DOORS AND FRAME HARDWARE TO MATCH EXIST. STOREFRONT SYS.



FRAME




EQUIPMENT AREA FRAME



LEAD SHIELDED

CLOSET FRAME

16 GA HMKD FRAME



LEAD SHIELDED

EQUIPMENT AREA

HMKD RE-USED DOOR AND FRAME AS COORDINATED BY CONTRACTOR

ARCHITECTS

HOFMANN ASSOCIATES, INC. 606 Baltimore Ave. Suite 102 Towson, Maryland 21204 410.828.9090

fax 410.828.4433

Professional Certification: I certify that these documents were prepared or approved by me, and that I am a duly licensed architect under the laws of the State of Maryland License Number: 3114 - A Expiration Date: 5 / 13 / 2015

くつかつ

CHESAPEAKE MEDICAL IMAGING

EDICAL ⋝ SAP

DEVELOPER / OWNER CHESAPEAKE I 1312 BELLONA / LUTHERVILLE, I CHE ISSUE DATE

11/03/14 PERMIT SET BID SET 1 11/20/14 ADDENDUM 1

THE CONCEPTS, IDEAS, DESIGNS AND IMAGES ARE INTENDED ONLY FOR THE PROJECT SPECIFIED ON THIS SHEET AND ARE THE SOLE PROPERTY OF HOFMANN ASSOCIATES, INC. THEY ARE NOT BE REPRODUCED OR USED BY OTHERS WITHOUT WRITTEN

> ASSOCIATES, INC. **SCHEDULES**

PERMISSION BY HOFMANN



project no.: 14-080

F-1 | CARPET W/ VINYL BASE PROVIDED | 4" VINYL COVE BASE PAINT (2) COATS FLAT THROUGHOUT OFFICE AREAS U.N.O. - AS SPECIFIED SHT. A-3 LATEX, - AS SPECIFIED SHEET A-3 - AS SPECIFIED SHEET A-3 $\lceil -2 \rceil$ 12"x12" V.C.T. BY ARMSTRONG OR EQUAL AS SELECTED BY OWNER. VINYL WOOD PLANK FLOORING - AS SPECIFIED SHEET A-3 E-X | EXISTING FINISH OR (NONE) (NONE) EXISTING CONCRETE SLAB

GENERAL NOTES:

FINISH SCHEDULE

- 1. PROVIDE 1" HORIZONTAL LOUVERED MINI-BLINDS (LEVELOR, BALI, RIVIERA OR EQUAL) FOR ALL EXTERIOR OFFICE WINDOWS.
- 2. PROVIDE ALLOWANCE FOR (2) FIRE EXTINGUISHERS THROUGHOUT OFFICE AREAS.

FLOOR COVERING SPECIFICATIONS

RESILIENT FLOORING (V.C.T.)

- A. VINYL COMPOSITION TILE TO CONFORM TO FS SS-T-312, TYPE IV.
- B. SIZE 12" X 12" X 1/8" GAUGE UNLESS OTHERWISE INDICATED. C. MULTICOLOR ARMSTRONG "EXCELLON", AZROCK OR APPROVED EQUAL. D. SUPPLY RESILIENT TRANSITION STRIP NOT LESS THAN 1" WIDE, MADE
- OF RUBBER, OR VINYL. E. LAY TILE FROM CENTER MARKS ESTABLISHED WITH PRINCIPAL WALLS. ADJUST TO AVOID USE OF CUT PIECES LESS THAN 1/2 TILE WIDTH
- AT PERIMETER. F. LAY TILE WITH GRAIN RUNNING IN THE SAME DIRECTION.

RUBBER WALL BASE

- A. TO CONFORM TO FS SS-W-40, 4" HIGH, 0.080" GAUGE WITH MATCHING STOPS AND PERFORMED CORNER
- UNITS; STANDARD TOP SET COVE, UNLESS OTHERWISE NOTED. B. ARMSTRONG, JOHNSONITE, NAFCO OR APPROVED EQUAL. APPLY IN THE LONGEST LENGTHS PRACTICAL FROM
- 120' ROLL STOCK. C. THE ONLY APPROVED JOINT IS A "BUTT JOINT".

<u>CARPET</u>

A. CARPET SHALL BE A MINIMUM OF 26 OZ. COMMERCIAL CARPET SOLUTION DYED NYLON OF TEXTURED LOOP CONSTRUCTION WITH A

C. ALL CARPET SHALL MEET THE MINIMUM ADA STANDARDS FOR STATIC

- WOVEN POLYPROPYLENE BACKING. B. FLAMMABILITY: PASS PILL TEST ASTM D 2859 (D) C FF-1-70.
- COEFFICIENT OF FRICTION OF 0.6 FOR ACCESSIBLE ROUTES. SMOKE TEST DENSITY OF 450 OR LESS, NFPA 258. E. INSTALLATION SHALL BE FULL CONTACT ONLY.