


GENERAL NOTES

- 1. SEE SPECIFICATIONS FOR PLUMBING PIPING INSULATION R-VALUE.
- 2. PROVIDE BACKWATER VALVE IN SANITARY LINE.
- 3. PROVIDE SHUT-OFF VALVE.
- 4. PROVIDE WATER HAMMER ARRESTORS FOR DISHWASHER AND WASHING MACHINE.
- 5. PROVIDE EXPANSION TANK TO SERVE HOT WATER HEATER.
- 6. PROVIDE ANTI-SCALD MIXING VALVE FOR TUB AND SHOWER. MAX TEMPERATURE: 120°F.
- 7. WATER TEMPERATURE CONTROLS SHALL BE PROVIDED ON WATER HEATER TO CONTROL TEMPERATURE BETWEEN 110°F AND MAX.

REFERENCED PLAN NOTES


- PIPE(S) BELOW FLOOR
 PIPE(S) ABOVE CEILING
 PIPE(S) UP TO FIXTURE
 PIPE(S) DN TO FIXTURE
 SEE RISER DIAGRAM FOR PIPE SIZES



PROFESSIONAL CERTIFICATION:

I HEREBY CERTIFY THAT THESE DOCUMENTS WERE PREPARED AND APPROVED BY ME, AND THAT I AM A DULY LICENSED PROFESSIONAL ENGINEER UNDER LAWS OF THE STATE OF MARYLAND.

LICENSE NO.: 43013 EXPIRATION DATE: 12-11-2020




SCALE: AS NOTED

DATE:

PROJECT NUMBER:

FLOOR PLANS



P101