

- 2: CEILING AND EQUIPMENT NOT SHOWN FOR CLARITY, COORDINATE WITH ARCHITECTURAL DRAWINGS.
- 3: EXIT, NIGHT, AND EMERGENCY LIGHTING ARE TO BE PROVIDED AND INSTALLED AS PER LOCAL CODE, COORDINATE WITH ARCHITECT

GROUND FLOOR - LOCH BAR - LIGHTING PLAN E.04 SCALE: 1/4" = 1'-0"

ARCHITECT

HapstakDemetriou +

ARCHITECTURE | DESIGN 2715 M STREET NW, 4th Floor 202.333.9038

www.hd-ad.com info@hd-ad.com

WASHINGTON, DC 20007

(410) 241-1224 afsmith11@gmail.com

CLIENT

Alexanader Smith

STRUCTURAL ENGINEER BEI Structural Engineers 3930 Pender Dr. Suite175 Fairfax, VA 22030

MEP ENGINEER J.B. Wyble and Associates, P.A. 7950 Norfolk Ave. , Bethesda, MD 301-654-1410

FOOD SERVICE CONSULTANT JLA Corp 13031 US Highway 19N,Clearwater, FL 33764 727-470-7862

OUZO BAY/ LOCH BAR HOUSTON

4444 WESTHEIMER RD, HOUSTON, TX 77027

PROJECT NO. JBW17108

I CERTIFY THAT THESE DOCUMENTS WERE PREPARED OR APPROVED BY ME, AND THAT I AM A DULY LICENSED PROFESSIONAL ENGINEER UNDER THE LAWS OF THE STATE OF TEXAS.

PE. LICENSE #: 129510, EXPIRATION DATE: DECEMBER 31, 2018 FIRM LICENSE #: F19615, EXPIRATION DATE: MARCH 31, 2019

REV DATE ISSUED FOR REV DATE **ISSUED FOR** 05/16/2018 PROGRESS SET 06/11/2018 PERMIT SET 08/30/2018 PERMIT COMMENTS

LOCH BAR GROUND FLOOR LIGHTING PLAN

E.04

LANDLORD NOTES:

1: ALL HOME RUNS TO TENANTS PANELS SHALL BE IN EMT.

City of Houston Texas

CON BOT TO TO THE AND EMERGENCY LIGHTS UNSWITCHED TO CIRCUIT SERVING LIGHTS IN SAME AREA

RECEPTACLE AT WINDOW, LOCATED EVERY 12' FEET, COORDINATE EXACT LOCATION WITH ARCHITECT

B DASHED LINE INDICATES DAYLIGHTING ZONE (2' TO EITHER SIDE OF OPENING, 15' IN TO SPACE) ALL LIGHTING INSIDE AREA TO BE CONTROLLED VIA SEPARATE DAYLIGHTING SENSOR (DS) AND DAYLIGHTING CONTROLLER (DC). OCCUPANCY SENSOR SHALL STILL MAINTAIN AUTOMATIC SHUT OFF

RECOLENS FOR DEPARTMENT ARCHITECT

VIA TIMECLOCK AND PHOTOCELL, (VERIFY)

CEILING/WALL MOUNTED MOTION SENSOR PROVIDE POWER
PERFORMANCE MAIN MOTION SENSOR PROVIDE POWER
REPORT OF MAIN MAIN MOTION SENSOR PROVIDE POWER
SENSORS TOGETHER TO CONTROL ALL LISHTS IN SAME AREA.

COOK MAIN TO BE
TO THE PERFORMANCE ON MODEL CHOSEN

- 2: ALL EXPOSED WIRING IN CEILINGS OR INTERIOR WALLS SHALL BE IN EMT. ALL WIRING IN LANDLORD DEMISING WALLS MUST BE IN EMT.
- 3: COORDINATE ALL FLOOR CUT MEANS AND METHODS OF ROUTING CONDUIT THROUGH THE FLOOR WITH MALL OPERATIONS.
- 4: NO CONDUIT TO BE SUPPORTED FROM THE ROOF DECK.
- 5: MOUNT ALL PANELS SURFACE MOUNTED ON PLYWOOD BACKERS. DO NOT MOUNT RECESSED WITHIN LANDLORDS DEMISING WALL.

JAMES B. WYBLE