



- Notes:**
1. Unlabeled conductors shall be 12-2-1/2" E.C. (Type 2 cable)
 2. Conductors with one bare conductor shall be 12-2-1/2" E.C. (Type 2 cable)
 3. Conductors with one bare conductor and one shielded conductor shall be 12-2-1/2" E.C. (Type 2 cable)
 4. Unshielded pairs - (Type 2 cable)
 5. In systems where an identification ring or color bands in conductors from head on wire shall be used.
 6. Conductors shall be bundled and secured to structure with wire ties.
 7. Conductors shall be secured to structure with wire ties.
 8. Conductors shall be secured to structure with wire ties.
 9. Conductors shall be secured to structure with wire ties.
 10. Conductors shall be secured to structure with wire ties.

General Note:
These drawings show the complete installation of the sound system. It is the responsibility of the contractor to verify the accuracy of the drawings and to comply with all applicable codes and regulations.

FIRE ALARM AND SOUND SYSTEMS

NOTRE DAME PREPARATORY SCHOOL
BALTIMORE COUNTY, MARYLAND
UPPER SCHOOL
FOR THE
SCHOOL SISTERS OF NOTRE DAME

TAYLOR AND FISHER ARCHITECTS
10 K. ST. FISHER, BALTIMORE, MARYLAND
130 W. HAMILTON ST., BALTIMORE 1, MD.

HENRY ADAMS, INC. - MECHANICAL ENGINEERS
MARTIN FINNELL - LANDSCAPE ARCHITECT

JOB NO. 1115
DATE: 09/11/58
DRAWING NUMBER
E-8
THIS PRINT ISSUED